

MYLANDS

ESTABLISHED LONDON 1884

PRODUCT DATA SHEETS QUICK DRYING KITCHEN & BATHROOM VARNISH

General	<p>Quick Drying Kitchen and Bathroom Varnish is good quality clear water-based alkyd varnish for interior use on wood and wood-based substrates. Formulated to resist moisture, staining and general wear and tear, QD Kitchen and Bathroom Varnish is ideal for those rooms where steam and moisture prevail.</p>		
Product Codes	<p>Product</p> <p>Quick Drying Kitchen & Bathroom Varnish</p> <p>Quick Drying Kitchen & Bathroom Varnish</p> <p>Quick Drying Kitchen & Bathroom Varnish</p>	<p>Product code</p> <p>126103090</p> <p>126103010</p> <p>126103030</p>	<p>Sheen</p> <p>Matt</p> <p>Satin</p> <p>Gloss</p>
Technical Data	<p>Quick Dry Kitchen and Bathroom Varnish is a water-based alkyd varnish for use on timber and wood-based substrates, it replaces an old oil based product but with no compromise on performance. It is only suitable for interior use and available in a matt, satin and gloss sheen. The product's speed of dry allows for two coats to be applied in one day.</p> <p>QD Kitchen & Bathroom Varnish is low odour and environmentally friendly, has good yellowing resistant properties, offers excellent resistance to mechanical damage and is completely washable. All the above properties make it an ideal product for use in kitchens and bathrooms where steam and moisture prevail. Additionally, QD Varnish is safe for use in areas where food is prepared.</p>		
Application	<p>Stir well before use.</p> <p>Do not use below 10°C or above 30°C. Do not use above 75% humidity.</p> <p>Ensure surfaces are sound, clean and dry before sanding and using QD Kitchen & Bathroom Varnish. If applying over bare wood, apply a thin even coat as a primer/sealer, this can be thinned with up to 10% water if required. Apply at least two or more unthinned coats depending on desired finish.</p> <p>QD Interior Varnish is formulated for brush or roller application, using coat-on-coat, lightly denib between coats with fine-grade sandpaper such as 240 or 320 lubrisil (201533124 & 201533132).</p>		
Drying Time	<p>The drying times quoted are at 20°C and will vary if temperature is higher or lower.</p> <p>Touch dry: 2 - 3 hours.</p> <p>Recoat time: 3 - 4 hours.</p>		
Coverage	<p>The coverage will vary depending on absorbency of substrate but should be an average of 8-10m² per litre.</p>		
Thinners	<p>QD Interior Varnish is supplied ready for use, but should it be deemed necessary to thin, water should be used up to a level of 10%.</p>		

Equipment Cleaning	Wash brushes/rollers in warm water containing a little detergent immediately after use.
Physical Constants	VOC level: 30g/litre.
Packaging	Mylands Quick Drying Interior Varnish is available in 1 litre and 2.5 litre containers as standard.
Health and Safety	Refer to Mylands Quick Drying Kitchen and Bathroom Varnish MSDS.

Updated 03/09/2018

For further information visit our website www.mylands.co.uk or contact us: +44 (0)208 670 9161 sales@mylands.co.uk